



SYN BLEND COMPRESSOR OIL ISO 100

Lubrication Oil

Syn Blend Compressor Oil ISO 100 is synthetic blended, high V.I. product designed to meet most compressor oil system needs.

It meets or surpasses pump manufacturers specifications for high-pressure applications, and will not shear out of grade. It will resist foaming and have good water demulsifying properties. These characteristics make it especially effective for compressor use.

Syn Blend Compressor Oil ISO 100 reduces pump wear and minimizes maintenance. It has outstanding oxidation resistance and is very stable to afford a long service life. In addition, Syn Blend Compressor Oil ISO 100 provides superior corrosion protection to safeguard equipment.

Features

- | | |
|----------------------------------|----------------------------------|
| • Versatile | ✓ Many applications |
| • Water and coolant resistant | ✓ Effective for machine tool use |
| • Can be used as Compressor oil | ✓ Low pump wear and maintenance |
| • Superior corrosion protection | ✓ Safeguard equipment |
| • Contains a defoamer package | ✓ Foam resistant |
| • Oxidation resistant and stable | ✓ Long service life |

Benefits

W.S. DODGE OIL
3710 FRUITLAND AVE. MAYWOOD, CA 90270
(323) 583-3478 F (323) 583-0950
www.wsdodgeoil.com



SYN BLEND COMPRESSOR OIL ISO 100

Lubrication Oil

Technical Data

(Typical properties)

Viscosity @ 40°C.,cSt	100
Viscosity @ 100 °F., SUS	500
Viscosity index (min.)	102
Flash Point, °C, (COC min.)	265
Pour point, °C.	-15
ISO Grade	100
Anti-wear Additives	no
Foam resistance	yes
Rust and oxidation resistance	yes
Color	clear yellow
Rust Test	pass

W.S. DODGE OIL
3710 FRUITLAND AVE. MAYWOOD, CA 90270
(323) 583-3478 F (323) 583-0950
www.wsdodgeoil.com